

Formatting Syntax

☞ DokuWiki supports some simple markup language, which tries to make the datafiles to be as readable as possible. This page contains all possible syntax you may use when editing the pages. Simply have a look at the source of this page by pressing “Edit this page”. If you want to try something, just use the [playground](#) page. The simpler markup is easily accessible via ☞ [quickbuttons](#), too.

Basic Text Formatting

DokuWiki supports **bold**, *italic*, underlined and monospaced texts. Of course you can **combine** all these.

DokuWiki supports **bold**, //italic//, __underlined__ and ''monospaced'' texts.

Of course you can **__//''combine''//__** all these.

You can use _{subscript} and ^{superscript}, too.

You can use _{subscript} and ^{superscript}, too.

You can mark something as deleted as well.

You can mark something as deleted as well.

Paragraphs are created from blank lines. If you want to **force a newline** without a paragraph, you can use two backslashes followed by a whitespace or the end of line.

This is some text with some linebreaks

Note that the two backslashes are only recognized at the end of a line

or followed by

a whitespace \\this happens without it.

This is some text with some linebreaks\\ Note that the
two backslashes are only recognized at the end of a line\\
or followed by\\ a whitespace \\this happens without it.

You should use forced newlines only if really needed.

Links

DokuWiki supports multiple ways of creating links.

External

External links are recognized automagically: <http://www.google.com> or simply www.google.com - You can set the link text as well: [This Link points to google](#). Email addresses like this one: andi@splitbrain.org are recognized, too.

DokuWiki supports multiple ways of creating links. External links are recognized automagically: <http://www.google.com> or simply www.google.com - You can set link text as well: [\[\[http://www.google.com|This Link points to google\]\]](#). Email addresses like this one: [<andi@splitbrain.org>](mailto:andi@splitbrain.org) are recognized, too.

Internal

Internal links are created by using square brackets. You can either just give a [pagename](#) or use an additional [link text](#).

Internal links are created by using square brackets. You can either just give a [\[\[pagename\]\]](#) or use an additional [\[\[pagename|link text\]\]](#).

⚠ Wiki pagenames are converted to lowercase automatically, special characters are not allowed.

You can use [namespaces](#) by using a colon in the pagename.

You can use [\[\[some:namespaces\]\]](#) by using a colon in the pagename.

For details about namespaces see [namespaces](#).

Linking to a specific section is possible, too. Just add the section name behind a hash character as known from HTML. This links to [this Section](#).

This links to [\[\[syntax#internal|this Section\]\]](#).

Notes:

- Links to [existing pages](#) are shown in a different style from [nonexisting](#) ones.
- DokuWiki does not use [CamelCase](#) to automatically create links by default, but this behavior can be enabled in the [config](#) file. Hint: If DokuWiki is a link, then it's enabled.
- When a section's heading is changed, its bookmark changes, too. So don't rely on section linking too much.

Interwiki

DokuWiki supports [Interwiki](#) links. These are quick links to other Wikis. For example this is a link to Wikipedia's page about Wikis: [Wiki](#).

DokuWiki supports [[doku>Interwiki]] links. These are quick links to other Wikis.

For example this is a link to Wikipedia's page about Wikis: [[wp>Wiki]].


Windows Shares

Windows shares like [this](#) are recognized, too. Please note that these only make sense in a homogeneous user group like a corporate [Intranet](#).

Windows Shares like [[\\server\share|this]] are recognized, too.


Notes:


- For security reasons direct browsing of windows shares only works in Microsoft Internet Explorer per default (and only in the “local zone”).
- For Mozilla and Firefox it can be enabled through different workaround mentioned in the [Mozilla Knowledge Base](#). However, there will still be a JavaScript warning about trying to open a Windows Share. To remove this warning (for all users), put the following line in conf/lang/en/lang.php (more details at [Localization](#)): <code - conf/lang/en/lang.php> <?php /* Customization of the english language file * Copy only the strings that needs to be modified */ \$lang['js']['nosmblinks'] = ; </code> ===== Image Links ===== You can also use an image to link to another internal or external page by combining the syntax for links and [images](#) (see below) like this:



Please note: The image formatting is the only formatting syntax accepted in link names. The whole [image](#) and [link](#) syntax is supported (including image resizing, internal and external images and URLs and interwiki links). ===== Footnotes ===== You can add footnotes ¹⁾ by using double parentheses. You can add footnotes ²⁾ by using double parentheses. ===== Sectioning ===== You can use up to five different levels of headlines to structure your content. If you have more than three headlines, a table of contents is generated automatically – this can be disabled by including the string ~~NOTOC~~ in the document. ===== Headline Level 3 ===== Headline Level 4 === Headline Level 5 == ===== Headline Level 3 === Headline Level 4 === Headline Level 5 == By using four or more dashes, you can make a horizontal line: --- ===== Media Files ===== You can include external and internal [images](#), [videos](#) and [audio files](#) with curly brackets.

Optionally you can specify the size of them. Real size:





Of course, you can add a title (displayed as a tooltip by most browsers), too.



For linking an image to another page see [Image Links](#) above. ===== Supported Media Formats ===== DokuWiki can embed the following media formats directly. | Image | gif, jpg, png | | Video | webm, ogv, mp4 | | Audio | ogg, mp3, wav | | Flash | swf | If you specify a filename that is not a supported media format, then it will be displayed as a link instead. By adding ?linkonly you provide a link to the media without displaying it inline [dokewiki-128.png](#) [dokewiki-128.png](#) This is just a link to the image. ===== Fallback Formats ===== Unfortunately not all browsers understand all video and audio formats. To mitigate the problem, you can upload your file in different formats for maximum browser compatibility. For example consider this embedded mp4 video: When you upload a video.webm and video.ogv next to the referenced video.mp4, DokuWiki will automatically add them as alternatives so that one of the three files is understood by your browser. Additionally DokuWiki supports a “poster” image which will be shown before the video has started. That image needs to have the same filename as the video and be either a jpg or png file. In the example above a video.jpg file would work. ===== Lists ===== Dokuwiki supports ordered and unordered lists. To create a list item, indent your text by two spaces and use a * for unordered lists or a - for ordered ones. * This is a list * The second item * You may have different levels * Another item - The same list but ordered - Another item - Just use indentation for deeper levels - That's it <code> * This is a list * The second item * You may have different levels * Another item - The same list but ordered - Another item - Just use indentation for deeper levels - That's it </code> Also take a look at the [FAQ on list items](#). ===== Text Conversions ===== DokuWiki can convert certain pre-defined characters or strings into images or other text or HTML. The text to image conversion is mainly done for smileys. And the text to HTML conversion is used for typography replacements, but can be configured to use other HTML as well. ===== Text to Image Conversions ===== DokuWiki converts commonly used [emoticons](#) to their graphical equivalents. Those [Smileys](#) and other images can be configured and extended. Here is an





DELETEME === Text to HTML Conversions === Typography: [DokuWiki](#) can convert simple text characters to their typographically correct entities. Here is an example of recognized characters. → ← ↔ ⇒ ← ↔ » « — — 640×480 © ™ ® “He thought 'It's a man's world'...” <code> → ← ↔ ⇒ ← ↔ » « — — 640×480 © ™ ® “He thought 'It's a man's world'...” </code> The same can be done to produce any kind of HTML, it just needs to be added to the [pattern file](#). There are three exceptions which do not come from that pattern file: multiplication entity (640×480), 'single' and "double quotes". They can be turned off through a [config option](#). === Quoting === Some times you want to mark some text to show it's a reply or comment. You can use the following syntax: <code> I think we should do it > No we shouldn't » Well, I say we should > Really? » Yes! »> Then lets do it! </code> I think we should do it > No we shouldn't » Well, I say we should > Really? » Yes! »> Then lets do it! === Tables === DokuWiki supports a simple syntax to create tables. ^ Heading 1 ^ Heading 2 ^ Heading 3 ^ | Row 1 Col 1 | Row 1 Col 2 | Row 1 Col 3 | | Row 2 Col 1 | some colspan (note the double pipe) || | Row 3 Col 1 | Row 3 Col 2 | Row 3 Col 3 | Table rows have to start and end with a | for normal rows or a ^ for headers. ^ Heading 1 ^ Heading 2 ^ Heading 3 ^ | Row 1 Col 1 | Row 1 Col 2 | Row 1 Col 3 | | Row 2 Col 1 | some colspan (note the double pipe) || | Row 3 Col 1 | Row 3 Col 2 | Row 3 Col 3 | To connect cells horizontally, just make the next cell completely empty as shown above. Be sure to have always the same amount of cell separators! Vertical tableheaders are possible, too. | ^ Heading 1 ^ Heading 2 ^ ^ Heading 3 | Row 1 Col 2 | Row 1 Col 3 | ^ Heading 4 | no colspan this time | | ^ Heading 5 | Row 2 Col 2 | Row 2 Col 3 | As you can see, it's the cell separator before a cell which decides about the formatting: | ^ Heading 1 ^ Heading 2 ^ ^ Heading 3 | Row 1 Col 2 | Row 1 Col 3 | ^ Heading 4 | no colspan this time | | ^ Heading 5 | Row 2 Col 2 | Row 2 Col 3 | You can have rowspan (vertically connected cells) by adding :: into the cells below the one to which they should connect. ^ Heading 1 ^ Heading 2 ^ Heading 3 ^ | Row 1 Col 1 | this cell spans vertically | Row 1 Col 3 | | Row 2 Col 1 | :: | Row 2 Col 3 | | Row 3 Col 1 | :: | Row 2 Col 3 | Apart from the rowspan syntax those cells should not contain anything else. ^ Heading 1 ^ Heading 2 ^ Heading 3 ^ | Row 1 Col 1 | this cell spans vertically | Row 1 Col 3 | | Row 2 Col 1 | :: | Row 2 Col 3 | You can align the table contents, too. Just add at least two whitespaces at the opposite end of your text: Add two spaces on the left to align right, two spaces on the right to align left and two spaces at least at both ends for centered text. ^ Table with alignment ^^^ | right| center |left | |left | right| center | | xxxxxxxxxxxx | xxxxxxxxxxxx | xxxxxxxxxxxx | This is how it looks in the source: ^ Table with alignment ^^^ | right| center |left | |left | right| center | | xxxxxxxxxxxx | xxxxxxxxxxxx | xxxxxxxxxxxx | Note: Vertical alignment is not supported. === No Formatting === If you need to display text exactly like it is typed (without any formatting), enclose the area either with <nowiki> tags or even simpler, with double percent signs %. This is some text which contains addresses like this: <http://www.splitbrain.org> and **formatting**, but

nothing is done with it. The same is true for `//__this__ text//` with a smiley ;-). This is some text which contains addresses like this: <http://www.splitbrain.org> and `**formatting**`, but nothing is done with it. The same is true for `//__this__ text//` with a smiley ;-). ===== Code Blocks ===== You can include code blocks into your documents by either indenting them by at least two spaces (like used for the previous examples) or by using the tags `<code>` or `<file>`. This is text is indented by two spaces. `<code>` This is preformatted code all spaces are preserved: like `<this > </code> <file>` This is pretty much the same, but you could use it to show that you quoted a file. `</file>` Those blocks were created by this source: This is text is indented by two spaces. `<code>` This is preformatted code all spaces are preserved: like `<this > </code> <file>` This is pretty much the same, but you could use it to show that you quoted a file. `</file>` ===== Syntax Highlighting ===== [DokuWiki](#) can highlight sourcecode, which makes it easier to read. It uses the [GeSHi](#) Generic Syntax Highlighter – so any language supported by GeSHi is supported. The syntax uses the same code and file blocks described in the previous section, but this time the name of the language syntax to be highlighted is included inside the tag, e.g. `<code java>` or `<file java>`. `<code java> / * The HelloWorldApp class implements an application that * simply displays "Hello World!" to the standard output. */ class HelloWorldApp { public static void main(String[] args) { System.out.println("Hello World!"); Display the string. } } </code>`

The following language strings are currently recognized: 4cs, 6502acme, 6502kickass, 6502tasm, 68000devpac, abap, actionscript-french, actionscript, actionscript3, ada, algol68, apache, applescript, asm, asp, autoconf, autohotkey, autoit, avisynth, awk, bascomavr, bash, basic4gl, bf, bibtex, blitzbasic, bnf, boo, c, cloadrunner, cmac, caddcl, cadlisp, cfdg, cfm, chaiscript, cil, clojure, cmake, cobol, coffeescript, cpp, cpp-qt, csharp, css, cuesheet, d, dcs, delphi, diff, div, dos, dot, e, epc, ecmascript, eiffel, email, erlang, euphoria, f1, falcon, fo, fortran, freebasic, fsharp, gambas, genero, genie, gdb, glsl, gml, gnuplot, go, groovy, gettext, gwbasic, haskell, hicest, hq9plus, html, html5, icon, idl, ini, inno, intercal, io, j, java5, java, javascript, jquery, kixtart, klonec, klonecpp, latex, lb, lisp, llvm, locobasic, logtalk, lolcode, lotusformulas, lotusscript, lscript, lsl2, lua, m68k, magiksf, make, mapbasic, matlab, mirc, modula2, modula3, mmix, mpasm, mxml, mysql, newlisp, nsis, oberon2, objc, objeck, ocaml-brief, ocaml, oobas, oracle8, oracle11, oxygene, oz, pascal, pcre, perl, perl6, per, pf, php-brief, php, pike, pic16, pixelbender, pli, plsql, postgresql, povray, powerbuilder, powershell, proftpd, progress, prolog, properties, providex, purebasic, pycon, python, q, qbasic, rails, rebol, reg, robots, rpmspec, rsplus, ruby, sas, scala, scheme, scilab, sdlbasic, smalltalk, smarty, sql, systemverilog, tcl, teraterm, text, thinbasic, tsql, typoscript, unicon, uscript, vala, vbnet, vb, verilog, vhdl, vim, visualfoxpro, visualprolog, whitespace, winbatch, whois, xbasic, xml, xorg_conf, xpp, yaml, z80, zxbasic ===== Downloadable Code Blocks ===== When you use the `<code>` or `<file>` syntax as above, you might want to make the shown code available for download as well. You can do this by specifying a file name after language code like this:

```
<code> <file php myexample.php> <?php echo "hello world!"; ?> </file>
```

</code> <file php myexample.php> <?php echo "hello world!"; ?> </file>
If you don't want any highlighting but want a downloadable file, specify a dash (-) as the language code: <code - myfile.foo>. ===== Embedding HTML and PHP ===== You can embed raw HTML or PHP code into your documents by using the <html> or <php> tags. (Use uppercase tags if you need to enclose block level elements.) HTML example: <code> <html> This is some inline HTML </html> <HTML> <p style="border:2px dashed red;">And this is some block HTML</p> </HTML> </code> <html> This is some inline HTML </html> <HTML> <p style="border:2px dashed red;">And this is some block HTML</p> </HTML> PHP example: <code> <php> echo 'The PHP version: ' ; echo phpversion(); echo ' (generated inline HTML)' ; </php> <PHP> echo '<table class="inline"><tr><td>The same, but inside a block level element:</td>' ; echo '<td>'.phpversion().</td>' ; echo '</tr></table>' ; </PHP> <code> <php> echo 'The PHP version: ' ; echo phpversion(); echo ' (inline HTML)' ; </php> <PHP> echo '<table class="inline"><tr><td>The same, but inside a block level element:</td>' ; echo '<td>'.phpversion().</td>' ; echo '</tr></table>' ; </PHP> Please Note: HTML and PHP embedding is disabled by default in the configuration. If disabled, the code is displayed instead of executed. ===== RSS/ATOM Feed Aggregation ===== DokuWiki can integrate data from external XML feeds. For parsing the XML feeds, SimplePie is used. All formats understood by SimplePie can be used in DokuWiki as well. You can influence the rendering by multiple additional space separated parameters: ^ Parameter ^ Description ^ | any number | will be used as maximum number items to show, defaults to 8 | | reverse | display the last items in the feed first | | author | show item authors names | | date | show item dates | | description| show the item description. If HTML is disabled all tags will be stripped | | nosort | do not sort the items in the feed | | n[dhm] | refresh period, where d=days, h=hours, m=minutes. (e.g. 12h = 12 hours). | The refresh period defaults to 4 hours. Any value below 10 minutes will be treated as 10 minutes. DokuWiki will generally try to supply a cached version of a page, obviously this is inappropriate when the page contains dynamic external content. The parameter tells DokuWiki to re-render the page if it is more than refresh period since the page was last rendered. By default the feed will be sorted by date, newest items first. You can sort it by oldest first using the reverse parameter, or display the feed as is with nosort. Example:

- [How Nintendo's Legal Team Destroyed Atari Games Through Courtroom Strategy](#) by msmash (2025/04/17 10:00)
- [LG TVs' Integrated Ads Get More Personal With Tech That Analyzes Viewer Emotions](#) by BeauHD (2025/04/17 07:00)
- [Astronomers Detect a Possible Signature of Life on a Distant Planet](#) by msmash (2025/04/17 04:30)
- ['We Are Not Programmed to Die,' Says Nobel Laureate Venki Ramakrishnan](#) by BeauHD (2025/04/17 03:30)
- [Microsoft Confirms Classic Outlook CPU Usage Spikes, Offers No Fix](#) by msmash (2025/04/17 02:30)
- [How Nintendo's Legal Team Destroyed Atari Games Through Courtroom Strategy](#) by msmash (2025/04/17 10:00)
- [LG TVs' Integrated Ads Get More Personal With Tech That Analyzes Viewer Emotions](#) by BeauHD (2025/04/17 07:00)

- [Astronomers Detect a Possible Signature of Life on a Distant Planet](#) by msmash
(2025/04/17 04:30)
- ['We Are Not Programmed to Die,' Says Nobel Laureate Venki Ramakrishnan](#) by BeauHD
(2025/04/17 03:30)
- [Microsoft Confirms Classic Outlook CPU Usage Spikes, Offers No Fix](#) by msmash
(2025/04/17 02:30)

===== Control Macros ===== Some syntax influences how DokuWiki renders a page without creating any output it self. The following control macros are available: ^ Macro ^ Description || ~~NOTOC~~ | If this macro is found on the page, no table of contents will be created || ~~NOCACHE~~ | DokuWiki caches all output by default. Sometimes this might not be wanted (eg. when the <php> syntax above is used), adding this macro will force DokuWiki to rerender a page on every call | ===== Syntax Plugins ===== DokuWiki's syntax can be extended by [Plugins](#). How the installed plugins are used is described on their appropriate description pages. The following syntax plugins are available in this particular DokuWiki installation:

- [Auto-Tooltip 2024-02-10](#) by [Eli Fenton](#)
Syntax and helper plugins for tooltips, including automatically generated tips based on page abstract.
- [caption plugin 2024-02-24](#) by [Till Biskup](#)
adding figure and table captions
- [Cells background color plugin 2013-10-09](#) by [dr4Ke](#)
Sets background of a cell with a specific color
- [Changes Plugin 2023-12-14](#) by [Andreas Gohr](#)
List the most recent changes of the wiki
- [DataTables Plugin 2023-08-31](#) by [Giuseppe Di Terlizzi](#)
Add DataTables support to DokuWiki
- [discussion plugin 2021-12-31](#) by [Michael Hamann, Gerrit Uitslag, Gina Häussge, Christopher Smith, Michael Klier, Esther Brunner, Matthias Schulte](#)
Provides discussion functionality for wiki pages
- [Draw.io plugin 2021-02-21](#) by [Milos Kozak](#)
Draw.io integration
- [Dw2Pdf plugin 2023-11-25](#) by [Andreas Gohr and Luigi Micco](#)
DokuWiki to PDF converter
- [Filelist Plugin 2024-03-13](#) by [Gina Häußge, Dokufreaks](#)
Lists files matching a given glob pattern.
- [Flowchartjs Plugin 2023-08-07](#) by [Hua Gao](#)
draw flowchart based on flowchart.js
- [Gallery Plugin 2023-12-08](#) by [Andreas Gohr](#)
Creates a gallery of images from a namespace or RSS/ATOM feed
- [Graphviz Plugin 2016-02-03](#) by [Andreas Gohr](#)
Create graph images from Graphviz dot language
- [iframe plugin 2023-08-17](#) by [Christopher Smith](#)
Allows external URLs to be loaded into an iframe in your DokuWiki page.
- [Info Plugin 2020-06-04](#) by [Andreas Gohr](#)
Displays information about various DokuWiki internals
- [Markdowku 2021-12-04](#) by [Julian Fagir, Raphael Wimmer \(maintainer\)](#)
Integrates Markdown into Dokuwiki syntax
- [MathJax plugin 2021-11-20](#) by [Mark Liffiton](#)
Enables MathJax (<https://www.mathjax.org/>) parsing of TeX math expressions in wiki pages

- [MediaList Plugin 2016-08-24 by Satoshi Sahara](#)
show a list of media files referred in a given page or stored in a given namespace.
- [nspages plugin 2024-01-04 by Guillaume Turri](#)
Presents a toc of the selected namespace using <nspages>
- [Pagebreak plugin 2016-02-16 by Jonathan McBride and Chris Sturm](#)
Inserts " <br style="page-break-after:always;"> " into the html of the document for every <pagebreak> it encounters
- [PDF.js 2020-06-29 by Szymon Olewniczak](#)
Show pdf files using PDF.js
- [PlantUML Parser 2023-11-02 by Kyle Carter](#)
This plugin takes PlantUML markup from a wiki page and has it displayed in a user's browser.
- [Sequencediagram plugin 2019-08-03 by K.-M. Hansche](#)
Generate sequence-diagrams
- [svgEmbed plugin 2021-06-09 by Michael Bowers](#)
Allows the use of the standard media syntax, but SVG files are placed with the <object> or <embed> tag, not the tag.
- [TextRotate Plugin 2021-10-24 by lisps, peterfromearth](#)
converts a string into an image and rotates it
- [TocTweak ver.2 2018-01-08 by Satoshi Sahara](#)
Show tailored table of contents (TOC) of specified page/section in the page content
- [ToDo 2024-03-04 by Leo Eibler, Christian Marg, Markus Gschwendt, Robert Weinmeister](#)
Create a checkbox based todo list with optional user assignment (by using <todo>This is a ToDo</todo>). In combination with dokuwiki searchpattern plugin it is a lightweight task list management system.
- [Wrap Plugin 2023-08-13 by Anika Henke](#)
Universal plugin which combines functionalities of many other plugins. Wrap wiki text inside containers (divs or spans) and give them a class (choose from a variety of preset classes), a width and/or a language with its associated text direction.

[1\)](#) [2\)](#)

This is a footnote

[3\)](#)

when the aspect ratio of the given width and height doesn't match that of the image, it will be cropped to the new ratio before resizing

From:

<https://wiki.astro.uni-koeln.de/wikis!/feedbacklegacyproject/> - **Feedback**

Permanent link:

<https://wiki.astro.uni-koeln.de/wikis!/feedbacklegacyproject/doku.php?id=wiki:syntax>

Last update: **2023/08/02 09:55**

